

GAS Discharge Tube Lightning Protector SMA Male / Female 0-3.0GHz

Feature:

- Excellent VSWR
- Low Insertion Loss
- Small compact size
- Replaceable Gas Tube

Picture:



Description	Specifications			
	79-0104	79-0104	79-0104	79-0104
Model	90V	145V	230V	470V
Frequency: (MHz) Range	DC- 3.0	DC- 3.0	DC- 3.0	DC- 3.0
Insertion Loss (dB)@2.5GH	<0.3	<0.3	<0.3	<0.3
Insertion Loss (dB)@3.5GHz	<0.35			
Input Return Loss (dB)	<-27	<-27	<-27	<-27
Output Return Loss (dB)	<-27	<-27	<-27	<-27
Impedance (ohm)	50	50	50	50
Connector	SMAM-F	SMAM-F	SMAM-F	SMAM-F
Temperature Range (C)	-10 /+60	-10 /+60	-10 /+60	-10 /+60
Weight (kg)	0.03	0.03	0.03	0.03
Size (mm)	49 x 25 x 22	49 x 25 x 22	49 x 25 x 22	49 x 25 x 22

Price: A\$35.5 (Excl. GST)

Please quote the special price for large quantity order

EYou Electronics Store is administered by RACOMTECH ABN: 79 068 236 054. 1 Fort street, Mount Waverley, VIC 3149, Australia

E-mail: sales@eyou.com.au Phone: +61-3-88029296 (Business Day)

GAS Discharge Tube Lightning Protector SMA Male / Female 0-3.5GHz

- Return Loss Test Results

