


## **1W Coax Termination SMA female**

## Model: SMA-F-12.4GHz-1W DC- 12.4 GHz 1Watt





Coaxial fixed terminations absorb RF & microwave energy and are commonly used as dummy loads of antenna and transmitter. They are also used as match ports in many multiport microwave devices such as circulator and directional coupler to make these ports which are not involved in the measurement be terminated in their characteristic impedance in order to ensure an accurate measurement.

SMAFE coaxial fixed termination average power 2W, frequency range dc-6GHz and feature wide frequency band, low VSWR, excellent capacity in antipulse and anti-burnout.

MECHANICAL SPECIFICATIONS						
CONNECTORS	Brass Nickel Plated					
PIN	Beryllium copper Gold Plate					
HOUSING	Brass Nickel Plated					
INSULATOR	PTFE Virgin Electrical Grade					
OPERATING TEMP.	-55° C to +125° C					
Dimensions (mm)	Ø7 x 14mm					
WEIGHT kg	5g					

RoHS compliant: Yes

## ELECTRICAL SPECIFICATIONS

Model	Frequency Range (GHz)	Power AVG(W)	Max VSWR
SMA-F-12.4GH-1W	DC – 12.4	1	≤1.2

Nominal impedance: 50Ω

AVERAGE POWER: 1W average to 25°C ambient temperature, derated linearly to 0.5W @ 125°C.
PEAK POWER: 0.25kW (5μs pulse width 0.8% duty cycle)
CONNECTOR TYPE: SMA (female)

## Notes:

- 1) Dimensions Tolerance ±5%
- 2) Dimension and specifications refer to connector type N unless otherwise specified
- 3) Customer designs available for other special attenuators value and accuracy